



Item	16mm	Description	Potential Problem	Measure	Recommended Inspection, Potential Replacement*	Latest Replacement after
System Joint						
1	SB9669-L0990	bearing nut (joint axis)	wear	replacing	every 6 months	36 months
2	SB6049-L0990	bearing nut (locking pawl)	wear	replacing	every 6 months	36 months
4	SK0373	locking pawl	wear of the teeth	replacing	every 3 months	12 months at activity level 1 and 2
						9 months at activity level 3
						6 months at activity level 4
5	GS1910-040	sliding washer, Ø = 19mm		replacing	every 6 months	18 months
5	GS1910-045		wear			
5	GS1910-050					
5	GS1910-055					
5	GS1910-060					
6	PN1000-L06	extension stop damper	wear	replacing	every 6 months	6 months
8	SK0363-2L	toothed ring with sliding bushing, left lateral or right medial, titanium	wear of the teeth	replacing	every 3 months	12 months at activity level 1 and 2
0	SK0363-2R	toothed ring with sliding bushing, left medial or right lateral, titanium				9 months at activity level 3
8	3KU3b3-2K					6 months at activity level 4
8a	BP1110-L059	sliding bushing	wear	replacing	every 6 months	18 months
9	SC1403-L08/1	countersunk flat head screw with hexalobular socket**	wear	replacing	every 6 months	36 months
12	SC1405-L14	countersunk flat head screw with hexalobular socket (axle screw)**		replacing	every 6 months	36 months
13	SC1404-L14	countersunk flat head screw with hexalobular socket**	wear			
9-13	SK3383-L	functional unit plug + go modularity left lateral or right medial*** loss of function,		average Company the	20	
9-13	SK3383-R	functional unit plug + go modularity left medial or right lateral***	wear	replacing	every 6 months	36 months
System Anchors and System Side Bars						
14	see catalogue	system anchor and system side bar	wear or breakage	replacing	every 6 months	if required

- \* depending on the assessment of the distributor of the custom-made product regarding the patient's usage behaviour
- \*\* is part of the functional unit
- \*\*\* included system components can be exchanged separately