

Item	16mm	Description	Potential Problem	Measure	Recommended Inspection, Potential Replacement*	Latest Replacement after
Syste	m Joint					
1	SB9669-L0760	bearing nut	wear	replacing	every 6 months	36 months
3	SF0393-02	feather key with pin	breakage	replacing	every 6 months	36 months
4	GS2210-040		wear	replacing	every 6 months	18 months
4	GS2210-045	sliding washer, Ø = 22mm				
4	GS2210-050					
4	GS2210-055					
4	GS2210-060					
5	SF0663-AL	cover plate**	wear	replacing	every 6 months	36 months
6a	VE3771-09/15	O-ring for securing the alignment screw**	wear	replacing	every 6 months	18 months
6c	FE1027-01	pressure spring**	wear	replacing	every 6 months	18 months
6d	GS1108-500	sliding bushing**	wear	replacing	every 6 months	18 months
6e	VE3771-012/26	O-ring damper**	wear	replacing	every 6 months	18 months
6f	SH0493-01	plunger**	wear	replacing	every 6 months	36 months
7	SC1405-L12	countersunk flat head screw with hexalobular socket**	wear	replacing	every 6 months	36 months
8	SC1405-L12	countersunk flat head screw with hexalobular socket (axle screw)**				
5-8	SF6973-AL	functional unit plug + go modularity***	loss of function, wear	replacing	every 6 months	36 months
Syste	m Stirrups, Syste	m Anchors and System Side Bars				
9	BR1110-L030	sliding bushing	wear	replacing	every 6 months	18 months
10	see catalogue	system stirrup	wear or breakage	replacing	every 6 months	48 months
11	see catalogue	system anchor and system side bar	wear or breakage	replacing	every 6 months	if required

^{*} depending on the assessment of the distributor of the custom-made product regarding the patient's usage behaviour

^{**} is part of the functional unit *** included system components can be exchanged separately